



Feature

- Vandalproof Dome Camera, 1/3" CMOS, 1080P, 2.0MP, 2.8-12mm varifocal lens, IR CUT, 30 LED, 30m IR, UTC Control, Coax Control by ANSON 1080P DVR

Dimensions

Technical Specifications

| | |
|-----------------------------------|---|
| Model NO. | AX-F200VAA-AHD |
| Image Device | 1/3" CMOS |
| TV System | PAL/NTSC |
| Total Pixels | 2.0 Megapixel |
| Resolution | 1920 (H) *1080 (V) |
| Scanning System | Progressive |
| Synchronization | Internal |
| Min. Illumination | 0 Lux (LED on) |
| S/N Ratio | >58db |
| Video Output | 1080PAHD/TVI/CVI or SD 960H OSD key switchable |
| LENS | |
| Focal Length | 2.8-12mm varifocal lens |
| OPERATIONAL(For OSD Model) | |
| LENS | MANUAL |
| Shutter | Auto,1/25-30(FLK) |
| AGC | 0-15 |
| SENS-UP | OFF/Auto |
| Brightness | 0-100 |
| D-WDR | ON/OFF |
| Backlight | ON/OFF |
| White Bal | ATW/Indoor/Outdoor |
| Day&Night | EXT/Color/B/W/Auto |
| IR Smart | Yes |
| 2DNR/3DNR | Yes |
| Language | Multi-Language |
| Defect | Live DPC/White DPC/Black DPC |
| Infrared LED | 30LEDs |
| IR Distance | 30m |
| IR-CUT | YES |
| Infrared Spectrum | 850nm |
| OPERATIONAL | |
| Operation Temperature | -10°C~ +50°C |
| Storage Temperature | -20°C~ +60°C |
| Water-proof Casing | IP66 |
| ELECTRICAL | |
| Adapter Requirement | DC12V1A |
| MECHANICAL | |
| Color | White |
| Net Weight | 800g/pcs |
| Transmission distance | 500meters(75-3) |