



**Feature**

- Vandalproof Dome Camera,8.0 MEGAPIXEL  
4X OPTICAL ZOOM IR, 3.6-11mm Motorized Lens, Auto Iris , 30M IR

**Technical Specifications**

<b>Model</b>	AX-K800VAA-IP
<b>Camera</b>	
Sensor/DSP	1/2.5" Progressive Scan CMOS
Day/Night	ICR
Image	WDR, 3D-DNR
Min. Illumination	0.001lux @F1.2 AGC on, 0lux with IR on
Lens	3.6-11MM Motorized lens
IR LED	30Leds
IR Distance	30m
Electronic Shutter	1/5~1/10000s
<b>Video</b>	
Compression	H.265
Max.image Resolution	8MP
Frame Rate	30FPS@3480X2160
Bit Rate	Main Stream: 1000~12000kps Sub Stream: 64~2048kbps
<b>Audio</b>	
Compression	G.711
Talkback	Support
<b>Network</b>	
Protocol	TCP/IP, UDP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP, NTP
Compliance	ONVIF V2.4(1.02 backward compatible)
PC Client and Browser	ISS, IE6.0 and above, Google Chrome, Mozilla Firefox, Mac Safari
Mobile phone	iPhone, iPad, Android
<b>Interface</b>	
Video Output	RJ45
Audio	Optional
Alarm	Optional
LAN	1 RJ45 10M / 100M Ethernet port
Storage Interface	Optional
<b>General</b>	
Working Temperature	-10°C~ +50°C
Working Humidity	0% - 90%
Protection Level	IP66 Vandalproof Dome
Power Supply	12 VDC ± 10%, POE(802.3af)
Weight	800g